US 20190154026A1

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2019/0154026 A1

Kamen et al. (43) Pub. Date: May 23, 2019

(54) **SYSTEM, METHOD, AND APPARATUS FOR INFUSING FLUID**

(71) Applicant: **DEKA Products Limited Partnership**, Manchester, NH (US)

(72) Inventors: **Dean Kamen**, Bedford, NH (US); **John M. Kerwin**, Manchester, NH (US); **Colin H. Murphy**, Cambridge, MA (US); **Larry B. Gray**, Merrimack, NH (US); **Christopher C. Langenfeld**, Nashua, NH (US); **Michael J. Slate**, Merrimack, NH (US); **Michael S. Place**, Manchester, NH (US)

(21) Appl. No.: **16/259,257**

(22) Filed: **Jan. 28, 2019**

Related U.S. Application Data

(63) Continuation of application No. 14/873,515, filed on Oct. 2, 2015, now Pat. No. 10,202,970, which is a continuation of application No. 13/725,790, filed on Dec. 21, 2012, now Pat. No. 9,677,555, which is a continuation-in-part of application No. 13/333,574, filed on Dec. 21, 2011, which is a continuation-in-part of application No. PCT/US11/66588, filed on Dec. 21, 2011, said application No. 14/873,515 is a continuation-in-part of application No. 13/723,238, filed on Dec. 21, 2012, now Pat. No. 9,759,369, which is a continuation-in-part of application No. 13/723,235, filed on Dec. 21, 2012, now Pat. No. 9,400,873, which is a continuation-in-part of application No. 13/724,568, filed on Dec. 21, 2012, now Pat. No. 9,295,778, which is a continuation-in-part of application No. 13/723,239, filed on Dec. 21, 2012, now Pat. No. 10,108,785, which is a continuation-in-part of application No. 13/723,242, filed on Dec. 21, 2012, which is a continuation-in-part of application No. 13/723,244, filed on Dec. 21, 2012, now Pat. No. 9,151,646, which is a continuation-in-part of application No. 13/723,251, filed on Dec. 21, 2012, now Pat. No. 9,636,455, which is a continuation-in-part of application No. 13/723,253, filed on Dec. 21, 2012.

(60) Provisional application No. 61/578,649, filed on Dec. 21, 2011, provisional application No. 61/578,658, filed on Dec. 21, 2011, provisional application No. 61/578,674, filed on Dec. 21, 2011, provisional application No. 61/679,117, filed on Aug. 3, 2012, provisional application No. 61/651,322, filed on May 24, 2012.

Publication Classification

(51) **Int. Cl.**

F04B 43/12	(2006.01)
G01F 1/66	(2006.01)
G06Q 50/22	(2006.01)
G16H 50/00	(2006.01)
G16H 20/17	(2006.01)
A61M 5/142	(2006.01)
G16H 40/63	(2006.01)
F04B 43/08	(2006.01)
A61M 5/168	(2006.01)

(52) **U.S. Cl.**

CPC ***F04B 43/1261*** (2013.01); ***G01F 1/666*** (2013.01); ***G06Q 50/22*** (2013.01); ***G16H 50/00*** (2018.01); ***G16H 20/17*** (2018.01); *A61M 2005/16863* (2013.01); ***G16H 40/63*** (2018.01); ***F04B 43/12*** (2013.01); ***F04B 43/082*** (2013.01); ***A61M 5/16831*** (2013.01); ***A61M 5/14228*** (2013.01)

(57) **ABSTRACT**

A peristaltic pump, and related system method are provided. The peristaltic pump includes a cam shaft, first and second pinch-valve cams, first and second pinch-valve cam followers, a plunger cam, a plunger-cam follower, a tube receiver, and a spring-biased plunger. The first and second pinch-valve cams are coupled to the cam shaft. The first and second pinch-valve cam followers each engage the first and second pinch-valve cams, respectively. The plunger cam is coupled to the cam shaft. The plunger-cam follower engages the plunger cam. The tube receiver is configured to receive a tube. The spring-biased plunger is coupled to the plunger-cam follower such that the expansion of the plunger cam along a radial angle intersecting the plunger-cam follower as the cam shaft rotates pushes the plunger cam follower towards the plunger and thereby disengages the spring-biased plunger from the tube. A spring coupled to the spring-biased plunger biases the spring-biased plunger to apply the crushing force to the tube.